



5-LOBE HANDWHEEL WITH BLIND THREADED BUSHING



FILE STEP
available online



material

GLASS-FIBER REINFORCED NYLON 6
RESISTANT TO OILS AND GREASES

standard color

BLACK

surface

SATIN

insert



BRASS BUSHING
(THREAD TOLERANCE 6G)

on request

• **STAINLESS STEEL BUSHING**
• **GALVANIZED STEEL BUSHING**

alternative colors

• **ORANGE** RAL 2004
• **BLUE** RAL 5015
• **YELLOW** RAL 1021
• **RED** RAL 3000
• **GREEN** RAL 6024
• **GREY** RAL 7035
• **BLACK** RAL 9011



CODE	TYPE	D	L	d	h	d1	l2
VOLBF5LNFN20M400	5VB/20 M4	20	16	M4	9,7	12	8
VOLBF5LNFN20M500	5VB/20 M5	20	16	M5	9,7	12	8
VOLBF5LNFN20M600	5VB/20 M6	20	16	M6	9,7	12	8
VOLBF5LNFN30M500	5VB/30 M5	30	21,5	M5	15	17	8,7
VOLBF5LNFN30M600	5VB/30 M6	30	21,5	M6	15	17	8,7
VOLBF5LNFN30M800	5VB/30 M8	30	21,5	M8	15	17	8,7
VOLBF5LNFN40M500	5VB/40 M5	40	27,5	M5	15,5	17	12,5
VOLBF5LNFN40M600	5VB/40 M6	40	27,5	M6	15,5	17	12,5
VOLBF5LNFN40M800	5VB/40 M8	40	27,5	M8	15,5	17	12,5
VOLBF5LNFN40I1000	5VB/40 M10	40	27,5	M10	15,5	17	12,5
VOLBF5LNFN50M600	5VB/50 M6	50	31	M6	15	22	11,5
VOLBF5LNFN50M800	5VB/50 M8	50	31	M8	15	22	11,5
VOLBF5LNFN50I1000	5VB/50 M10	50	31	M10	15	22	11,5
VOLBF5LNFN50I1200	5VB/50 M12	50	31	M12	15	22	11,5
VOLBF5LNFN60M800	5VB/60 M8	60	32,5	M8	15	25	9,5
VOLBF5LNFN60I1000	5VB/60 M10	60	32,5	M10	15	25	9,5
VOLBF5LNFN60I1200	5VB/60 M12	60	32,5	M12	15	25	9,5

(mm)