



FILE STEP
available online

SPRING PLUNGER WITH NOTCH AND BALL STAINLESS STEEL



Version - M06
Original size - 4 mm

MATERIAL

Stainless steel
Body 1.4305
Ball 1.4034
Spring 1.4310

DESIGN



Untreated surface. Hardened ball.

INDICATIONS

Quick indexing, positioning, and clamping of components

AREAS OF USE

Machinery construction, plant construction, crafts, household.
Universal use and easy to assemble.



$a=60^\circ$, $F' = 1,732 \times F$
 $a=90^\circ$, $F' = F$
 $a=120^\circ$, $F' = 0,577 \times F$

COD.	Elastic force	D	L	D1	H	N	Elastic force beginning F1	Elastic force end F1
PRESATSAI0M3700	standard	M3	7	1,5	0,4	0,4	1,5	3
PRESATSAI0M4900	standard	M4	9	2,5	0,8	0,6	4	10
PRESATSAI0M5200	standard	M5	12	3	0,9	0,8	6	11
PRESATSAI0M6400	standard	M6	14	3,5	1	1	9	13
PRESATSAI0M8600	standard	M8	16	5	1,5	1,2	15	30
PRESATSAI0M10900	standard	M10	19	6	2	1,6	20	35
PRESATSAI0M12200	standard	M12	22	8	2,5	2	30	55
PRESATSAI0M16400	standard	M16	24	10	3,5	2,5	65	125
PRESATSAI0M20000	standard	M20	30	12	4,5	2,5	80	160
PRESATPAI0M3700	enhanced	M3	7	1,5	0,4	0,4	5	7
PRESATPAI0M4900	enhanced	M4	9	2,5	0,8	0,6	12	22
PRESATPAI0M5200	enhanced	M5	12	3	0,9	0,8	19	30
PRESATPAI0M6400	enhanced	M6	14	3,5	1	1	28	40
PRESATPAI0M8600	enhanced	M8	16	5	1,5	1,2	47	73
PRESATPAI0M10900	enhanced	M10	19	6	2	1,6	66	100
PRESATPAI0M12200	enhanced	M12	22	8	2,5	2	66	120
PRESATPAI0M16400	enhanced	M16	24	10	3,5	2,5	90	180
PRESATPAI0M20000	enhanced	M20	30	12	4,5	2,5	115	240

(mm)